

Bar Refrigeration

TBR36-PTSZ1-L-S-S-S-2

■ "Pass-Thru" Bar Refrigerator, Stainless Steel Ext, 1 Solid Swing Door Front, 1 Solid Swing Door Rear



Dimensions	
External Width (mm)	914
External Depth (mm)	631
External Height (mm)	881
Exclusions	Depth does not include 35 mm for front + 35 mm for back door handles. Height does not include 7 mm for leg levelers.
Gross Volume (Litres)	350
Supplied Shelves	3
Shelf Size (L x D mm)	394 x 458
Internal Net Height (mm)	730
Unpackaged Weight (kg)	121
Packaged Weight (kg)	132
Packaged Dimensions (W x D x H mm)	1083 x 801 x 1067
Supplied with	Levelling Screws. Optional castors sold seperately.

Build	
Door Description	1 Solid Swing Door
Door Opening	Left (standard) or Right Field Reversible
Exterior Construction	Stainless Steel front and countertop. Matching Aluminium sides & rear.
Interior Construction	Stainless Steel
Air Intake Position	Front
Ventilation Position	Front
Clearance Required	Zero back and sides
Cord Length (Meters)	3.04
Internal Lighting	LED
Standard w/ Locks	Standard

Technical	
Temperature Range	0.5 : 3.3°C
Refrigerant	R290
Voltage/Frequency/Phase	220-240V/50-60Hz/1
Amps	1.8
Watts	414
Defrost Type	Auto



Specifications subject to change without notice.
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland
EMEA
Australia

0800 783 2049
[+41 61 563 07 05](tel:+41615630705)
[+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



Technical drawings of the R22 31/32 inch condensing unit, showing dimensions in inches and millimeters.

Front View:

- Overall Width: 36" [914]
- Overall Height: 34 11/16" [881]
- Top Flange Thickness: 1 3/4" [44]
- Right Side Flange Thickness: 2 7/32" [56]
- Internal Height (to door opening): 31 11/16" [805]
- Bottom Flange Thickness: 11 19/32" [294]
- Door Opening Width: 23 5/8" [600]
- Door Opening Height: 25/32" [20]
- Door Opening Dimensions: 20 9/32" [515] X 28 5/16" [719]
- Label: DOOR OPENING
- Label: POWER CORD EXIT

Side View:

- Overall Width: 30" [762]
- Overall Height: 30 27/32" [783]
- Top Flange Thickness: 26 15/16" [684]
- Internal Height (to door opening): 22 3/4" [578]
- Door Opening Width: 22 3/4" [578]
- Door Opening Height: 3 15/16" [100]
- Bottom Flange Thickness: 4 5/16" [110]
- Label: ACCESS OPPOSITE CONDENSING UNIT

Top View:

- Overall Width: 16 3/4" [425]
- Overall Height: 72 13/32" [1839]
- Left Side Flange Thickness: 7 1/32" [179]
- Right Side Flange Thickness: 6 13/32" [163]
- Internal Width (to floor access): 20 13/32" [518]
- Internal Height (to drain access): 18 3/4" [476]
- Internal Width (to drain access): 22 23/32" [577]
- Internal Height (to drain access): 20 13/32" [518]
- Label: FLOOR ACCESS
- Label: DRAIN ACCESS
- Label: R22 31/32" [583]



Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com

